



## Product Specification

Product Name: **PORTER'S ALL PURPOSE CLEAR SEALER**

---

### PRODUCT DESCRIPTION:

Porter's All Purpose Clear Sealer is an interior use sealer that is suitable for floors, walls and furniture and is the only clear sealer recommended as a protective clear sealer for use over Porter's Milk Paint and Porter's Fresco. It is quick drying and resists yellowing, drying to a beautiful satin finish. Although All Purpose Clear Sealer is suitable for floors, we would recommend Porter's Clearcote as a better choice on floors, as it is much stronger and designed specifically for this use.

### LOCATION:

Interior.

### SUGGESTED APPLICATIONS:

Can be applied to most suitably prepared interior timber, floors and furniture. Suitable for use as a protective clear sealer for use over Porter's Milk Paint and Porter's Fresco.

### COLOUR:

Appears milky white in can, dries clear.

### LIMITATIONS:

Test before use as a slight colour variation may occur.

Not suitable for use over previously oiled timbers. Test before use on timber with a high tannin content. Normally tannin bleed is undetectable, but if you are using All Purpose Clear Sealer over a finish such as Wood Wash or Milk Paint tannin bleed may be visible as a slight brown staining. Tannin bleed does not affect product performance.

Not suitable for use in wet areas.

Do not apply in high humidity, below 10°C or above 30°C.

### PREPARATION:

The substrate should be a clean well-held surface free from loose material, dirt, dust, grease, oil and mould. Dust down before proceeding. Allow all paints and finishes to a dry a minimum of 72 hours prior to the application of Porter's All Purpose Clear Sealer. When being applied as a floor sealer, vacuum prior to application.

## APPLICATION:

Stir thoroughly prior to use. Apply 2 to 3 coats by brush, or lambs' wool applicator (recommended for floors). Touch dry in 2 hours. Allow minimum 12 hours dry time between coats. Sand lightly between coats to remove any raised grain. Vacuum to remove dust before applying another coat. Allow 24 hours before allowing light foot traffic on floor surfaces. Full cure is achieved in 7 days.

## COVERAGE RATES:

Covers approximately 15m<sup>2</sup> per litre, depending upon porosity, surface texture and wastage rates.

## WASH UP:

Water.

## COMPLEMENTARY PRODUCTS:

Porter's All Purpose Clear Sealer is compatible for use over Porter's Milk Paint and Porter's Fresco.

## PACKAGING:

Porter's All Purpose Clear Sealer is available in 1 litre, 4 litre & 15 litre sizes.

## STORAGE:

Store in a cool dry area, protected from frost.

## PRECAUTIONS:

Keep out of reach of children. Avoid swallowing. Avoid eye contact. Avoid prolonged skin contact. Provide adequate ventilation. If accidental contact occurs, rinse immediately with water.

## MANUFACTURER'S/DISTRIBUTOR'S DETAILS:

Porter's Paints  
288 Coward St  
Mascot NSW 2020  
Australia

Phone: (02) 9698-5322  
Toll free: 1800 656 664  
Fax: (02) 9699-5322  
E-mail: [enquiries@porters.com.au](mailto:enquiries@porters.com.au)  
Web: [www.porterspains.com](http://www.porterspains.com)

Porter's Paints  
150 Hutt Park Rd  
Gracefield  
Lower Hutt 5010  
New Zealand  
Ph: 0800 672 468